

# Forecasting the change of soil moisture in Caragana Shrubland using wavelet analysis and NARX neural network

Wing Yang\*, Sang Min Lee

Yang W, Lee SM. Forecasting the change of soil moisture in Caragana Shrubland using wavelet analysis and NARX neural network. *AGBIR*.2023;39(5):634-638.

It is important for sustainable use of soil water resource and high-quality development to forecast the change of soil moisture in forestland of water-limited regions. There are some soil moisture models. However, there is not the best model to forecast soil moisture. In this paper, the plant water relationship has been investigated for a long term in the Caragana shrubland of semiarid region of the Loess Plateau of China. The data of soil moisture was divided into a low frequency and a high frequency component using wavelet analysis, and then NARX neural network was used to build model I

and model II. For model I, low frequency component was the input variable, and for model II, low frequency component and high frequency component were predicted. The results showed the average relative error for model I is 3.5% and for model II is 0.3%. The average relative error of predicted soil moisture in 100 cm layer using model II is 0.8%, then soil water content in the 40 cm and 200 cm soil depth is selected and the forecast errors are 4.9% and 0.4%. The result showed that using model II to predict soil water is well. Predicting soil water using model II will be important for sustainable use of soil water resource and high-quality development.

**Key Words:** Semi-arid loess hilly region; Wavelet analysis; NARX recurrent neural network; Soil moisture forecast; High-quality development

## INTRODUCTION

Soil moisture is one of the most basic elements of the soil fertility and the foundation for the crop fertility and high-quality development. The soil water resources are the soil water storage in a given soil depth, and soil water resources use limit by plant refers to the amount of water stored within the maximum infiltration depth, in which the soil moisture content in each layer is equal to the withering coefficient. When soil water resources in the maximum infiltration depth reduce to the soil water resources use limit by plant, soil drought is serious, which cause serious soil degradation, vegetation decline and crop failure because the limit of soil water vegetation carrying capacity. At this stage of plant growth, the plant water relationship has to be regulated and to get maximum yield and service and carry out high-quality development. So, soil moisture has been highly considered. Predicting the dynamics of soil moisture is the foundation for sustainable use of soil water resources and soil water management, drought assessment and yield estimation. There are different kinds of soil moisture models such as water balance model, the SPAC water transport model, the SPAC water heat transport model, the mathematical statistics model, the random water balance model and the stochastic soil water dynamics model and so on. Because meteorology, soil and crops have some random features in time and space, it is difficult to select the modeling parameters to predict [1].

Artificial Neural Network (ANN) is an analysis method dealing with global and nonlinear mapping relationship between inputs and outputs. Because of self-organizing, self-learning and redundant fault-tolerant properties of the input data, ANN has a great advantage in the data fitting and function approximation and have widely been applied [2-4], such as the prediction of soil moisture [1,4-6].

As a kind of LAN transformation of time and frequency, Wavelet analysis can extract the information effectively in the signal, and proceeds multi-scale refinement analysis of signal through scaling and translation to realize the high-resolution local positioning of the time domain and frequency domain. Combining with the artificial neural network and wavelet analysis method, wavelet neural network method has two sides of advantages and widely applied in the hydrological forecasting [7], water quality prediction [8] and so on. However, there are a few reports of the application of wavelet neural network method in soil moisture forecast, especially the predict accuracy of

soil water content in forest land. In this paper, authors try to use wavelet and neural network model to forecast the soil moisture in Caragana shrubland. The results will provide a powerful basis for estimating the soil water resources use limit by plants, soil water vegetation carrying capacity and the regulation of the relationship between plant growth and soil water and the vegetation restoration in loess hilly region [9].

## MATERIALS AND METHODS

### Site description

This study was carried out at the Shanghuang Eco-Experiment Station, located in the semiarid region of the Loess Plateau (35°59'36"02" N, 106°26'106"30"E) in Guyuan, Ningxia Hui Autonomous Region, China. The altitude ranges from 1,534 to 1,824 m above the sea level. Precipitation is scarce in the period from January to March, and the rainfall from June to September accounts for more than 70% of the annual precipitation. Mean rainfall measured between 1983 and 2001 was 415.6 mm with a maximum of 635 mm in 1984 and a minimum of 260 mm in 1991. The frost-free period is 152 days. The soil is mainly loamy loess [10], which is porous and widely distributed in the semiarid region of the Loess Plateau. There is a little change of soil texture with the depth in the soil profile [11]. The experimental field was located in the Caragana bushland in the middle of Heici Mountain with a slope gradient of 8°, facing southeast at the station. The study object is 16-year-old Caragana (*Caragana korshinskii*) Plantation, under which the main plant species are *Stipa bungeana*, *Heteropappus altaicus*, *Artemisia giraldii* and *Thymus mongolicus*.

### Measurement

The investigation of the existing Caragana shrubs was made at the study site in April of 2002. There are five 100 m<sup>2</sup> (5 × 20 m) standard runoff plots. The sowing amounts of Caragana were 2.0 kg, 1.5 kg, 1.0 kg, 0.5 kg and 0 kg/100 m<sup>2</sup> (wasteland, control), respectively. A neutron probe, CNC503A (Beijing Nuclear Instrument Company, Beijing), was used to measure soil moisture in the soil layers from 5 cm to 780 cm and measurement was made at every 20 cm interval. The soil water content obtained for each measuring depth was taken to be representative for the soil layer that included the measuring point ± 10 cm depth, apart from that for the 5 cm depth, which was taken to represent the upper 10 cm of soil. Neutron counts were made for 16 seconds.

Department of Agricultural Biology, Jeonbuk National University, Jeonju, Republic of Korea

**Correspondence:** Wing Yang, Department of Agricultural Biology, Jeonbuk National University, Jeonju, Republic of Korea, Email: wingyang4219@gmail.com

**Received:** 16-Aug-2023, Manuscript No. AGBIR-23-110425; **Editor assigned:** 18-Aug-2023, Pre QC No. AGBIR-23-110425 (PQ); **Reviewed:** 04-Sep-2023, QC No. AGBIR-23-110425; **Revised:** 13-Sep-2023, Manuscript No. AGBIR-23-110425 (R); **Published:** 20-Sep-2023, DOI:10.35248/0970-1907.23.39.634-638



This open-access article is distributed under the terms of the Creative Commons Attribution Non-Commercial License (CC BY-NC) (<http://creativecommons.org/licenses/by-nc/4.0/>), which permits reuse, distribution and reproduction of the article, provided that the original work is properly cited and the reuse is restricted to noncommercial purposes. For commercial reuse, contact [reprints@pulsus.com](mailto:reprints@pulsus.com)

The growing season of Caragana was in the period from April to October every year. Measurement was made at 15 days' interval in growing season and one time per month in the period of dormancy. This paper selects the soil water contents measured in the experimental plot with the sowing amount of 1.5 kg/100 m<sup>2</sup> as the research object to analysis and predict the dynamics of soil moisture in Caragana brushland.

**Data process**

The MATLAB software was used to process the data. The data measured in this study basically reflect the soil moisture dynamic change trend, but it is short for neural network training and wavelet analysis, so cubic spline interpolation method was used to enlarge the measure frequency to one time a week and then got 113 sets of data.

**Wavelet analysis**

Wavelet analysis, a kind of mathematical method based on Fourier analysis, can show the subtle structure and characteristics of measured data using wavelet transform through selecting proper scale and window functions. Wavelet transformation needs to choose suitable wavelet function such as Haar, Daubechies, Symlets, Coiflets and so on. The Daubechies wavelet function can be used to better analyze the problems of time series reported by Zhou and Gui [12].

**NARX recursive neural network**

Nonlinear Auto-regressive with Exogenous Inputs Model (NARX network) 1 was a kind of recursive neural networks with delay unit and was referred to the nonlinear auto-regressive models with external input. The input layer of the network receives two kinds of signals. The inputs from the outside the network can be expressed as  $u(k), u(k-1), \dots, u(k-p+1)$ , and the outputs of feedback signals from the network can be expressed as  $y(k), y(k-1), \dots, y(k-p+1)$ , and the nonlinear system of network dynamic can be expressed as  $y(k+1)=F(y(k), \dots, y(k-p+1), u(k), \dots, u(k-p+1))$ . The NARX network training algorithm adopted LM algorithm of BP network.

**Model**

Soil water data were divided and reconstruct based on the wavelet analysis method, and then authors got the general picture of the low-frequency components and high-frequency details. In model I, authors selected the low frequency component and the soil water content in a soil layer which is highly correlated with that in the predicted soil layers as input variables to build NARX recursive neural network prediction model I according to wavelet analysis. In Model II: NARX neural network was used to predict the general picture of low-frequency components and high frequency detail respectively, and then we have got the soil moisture forecast results by summing the network outputs.

**RESULTS AND DISCUSSION**

**Selection of target layers**

The soil moisture contents in 5 to 300 cm soil layers were selected as the research target. The variation coefficient of soil moisture content in each soil layer were estimated. The variation coefficient of soil moisture content in 5 cm soil layer,  $CV_5$ , is more than 30%, that is to say,  $CV_5 > 30\%$ ,  $20\% < CV_{20-80} < 30\%$ ,  $5\% < CV_{100-180} < 20\%$ ,  $CV_{200-300} < 5\%$ , respectively, so the 5 to 300 cm soil layers can be classified into four groups, 0 to 5 cm, 20 to 80 cm, 80 to 180 cm and 200 to 300 cm soil layer. Because soil moisture content in the 5 cm soil layer is surface soil and interfered by outside factors and the change trend of soil water in the soil layer was uncertainty in Caragana brushland, it was not being selected as the research target. Finally, the soil water contents in the rest three soil layers such as 40 cm, 100 cm and 200 cm soil layers were chosen respectively as the analysis object.

**Wavelet analysis of soil moisture**

First, the soil water content in the 100 cm layer were selected as the research objects, and the interpolated 113 sets of data in 100 cm layer were selected as the original wavelet sequence  $s_1$ , then db2 was selected to do single scaling wavelet decomposition and reconstruction [13,14], as shown in Figure 1.




Figure 1) Results of wavelet analysis of soil water content in 100 cm soil layer

In Figure 1,  $s_1$  is time series trend diagram of soil moisture data measured in 100 cm soil layer,  $a_1$  is the general picture part of low frequency and its variation trend is consistent with the original signal. The high frequency detail part is  $d_1$  after soil water data were decomposed using single scale wavelet, which reflects the change of the original signal frequency.  $s_1$ ,  $s_1 = a_1 + d_1$ , is the synthesized reconstruction signal of decomposed by single scaling wavelet.

**The selection of input variable**

This article selected the soil moisture content in the soil layers that highly correlated with  $s_1$  as the inputs, the correlation results at each soil layer are shown in Table 1. Besides,  $a_1$  can be used as an input because it has the similar dynamic change trend with  $s_1$ , so input variables of model I were as follows: 60 cm, 80 cm, 120 cm, 140 cm,  $a_1$  and output variables was  $s_1$ .

The selection of input variables in model II: (1) when predicting  $a_1$ , the soil water contents in 60 cm, 80 cm, 100 cm, 120 cm and 140 cm soil layers were inputs,  $a_1$  was outputs; (2) when predicting  $d_1$ ,  $s_1$  is only related to  $s_1$ ,  $d_1$  was output variable.

**Comparison between model I and model II**

The range of soil moisture content was volatile due to much affecting factors, so this article was only used for short-term prediction. The input variables of week N and output variables of week N+1 form a sample set, and there was a total of 112 samples sets. Data sets was divided as follows: the data from 1 to 90 groups was taken as the training set, which used for fitting model; the data from 91 to 101 sets was taken as the validation set, which used for the prediction of error estimation in the selected model; the remaining data in II sets be used as a test set to ultimately evaluate the generalization error of selected model.

Figure 2 showed the simulation correlation analysis in training set  $s_1$  for model I and model II of  $d_1$  is only related to  $s_1$ ,  $d_1$  was output variable. It can be seen from Figure 2 that model II was better than model I in the overlap of the simulated values predicting  $d_1$ ,  $s_1$  was input variable for the change and the measured values and in the correlation analysis, showing that the NARX recursive neural network has better learning ability than BP neural network.

**TABLE 1**  
The correlation analysis among soil water contents in 40 cm to 160 cm soil layers

Soil layer (cm)	40	60	80	100	120	140	160
40	1	0.893	0.717	0.423	0.375	0.32	0.177
60	0.893	1	0.889	0.616	0.525	0.416	0.228
80	0.717	0.889	1	0.683	0.62	0.51	0.323
100	0.423	0.616	0.683	1	0.892	0.711	0.229
120	0.375	0.525	0.62	0.892	1	0.923	0.431
140	0.32	0.416	0.51	0.711	0.923	1	0.598
160	0.177	0.228	0.323	0.229	0.431	0.598	1




Table 2 is the validation set of forecast error analysis for the model I and model II. It can be seen from the Table 2 that average relative error of model I was 3.5% and that of model II was 0.3%, showing that the prediction accuracy using the model II are higher than that using model I.

**Table 2**  
**Comparison of predicted error of validation set**

Items	Relative error (%)	Items	Relative error %
92	6.99	99	-3.27
93	5.98	100	-4.75
94	6.27	101	2.68
95	10.9	102	4.77
96	5.56		
97	-0.08	<b>Average relative error (%)</b>	<b>3.52</b>
98	3.66		

**The applicant of model II**

In order to study the feasibility of actual operation of model II, in the paper soil water content from 103 to 113 weeks in the 100 cm soil layer were forecasted, as shown in Table 3.

**Table 3**  
**Comparison of predicted error and observed values from 103 to 113 week in 100 cm soil layer**

Week	Observed	Week	Observed
103	6.8622	6.8836	0.31
104	6.8289	6.8951	0.97
105	6.6937	6.7091	0.23
106	6.4809	6.4841	0.05
107	7.1149	7.1138	-0.02

**Table 4**  
**Error analysis of the predicted values from 103 to 113 week at 40 cm and 200 cm soil layers**

Items		40 cm		20 cm	
Week	Actual data	Week	Actual data	Week	Actual data
103	6.862	6.4253	-6.37	6.314	6.2957
104	6.123	5.914	-3.41	6.327	6.2908
105	6.704	6.2114	-7.35	6.357	6.3538
106	13.05	12.66	-3.02	6.358	6.3704
107	16.73	16.518	-1.26	6.399	6.3696
108	17.48	17.353	-0.74	6.537	6.5047
109	13.78	12.784	-7.23	6.652	6.6998
110	13.43	15.053	12.06	6.627	6.6682
111	11.96	12.717	6.35	6.525	6.54
112	11.05	10.554	-4.45	6.455	6.4755
113	9.389	9.7211	3.53	6.525	6.4913
Average error (%)			Average error (%)		

108	9.2415	9.2373	-0.05
109	11.4952	11.5012	0.05
110	12.4359	12.4043	-0.25
111	12.3375	12.2879	-0.4
112	11.9021	11.3647	-4.52
113	11.832	12.077	2.07
Average relative error(%)			0.81

Based on wavelet analysis, the model II was more suitable than model I for forecasting soil water content in the Caragana shrubland by comparing the results of correlation analysis of simulated and measured values and the prediction error analysis of validation set.

The average relative error of predicted soil water from 103 to 113 weeks is 0.8%, and absolute values of relative error of soil water in the 11 weeks were lower than 10%, showing that model II is feasible in prediction of soil water content in the woodland.

The model after training (learning) right reflects the samples that did not occurred in training set. Learning is not simply to memorize the studied inputs, but to learn the inner regularity of environment itself embedded in the sample through the study of a finite number of being trained samples 16. In order to further test the model generalization ability, moisture contents from 103 to 113 weeks in 40 cm and 200 cm soil layer were predicted. The correlation analysis of the predicted values and the measured values were shown in Figure 2. The error analysis of prediction values was shown in Table 4.

The Table 4 showed that the curves of predicted values were consistent with the measured values in 40 cm and 200 cm soil layer. The correlation coefficient of the linear regression equation was 0.981, 0.984 respectively, and  $p < 0.05$ . The average relative errors were less than 5%, suggesting that the wavelet neural network model II has good generalization performance.

## Discussion

After the original signal were divided into low-frequency components and high-frequency components, wavelet analysis was used to analyse the data, and fully highlighted the trend and frequency fluctuations of signals changing with time, and avoided bad learning problems of some high-frequency mutation data when directly using neural network to predict the original data.

The low-frequency component of the soil water content after wavelet analysis in the soil layers largely correlated with that were selected as the input variables in Model I to predict soil general picture of the low-frequency water content in target soil layer. Model II used NARX recursive neural network to predict the component and high frequency detail component, then combined the outputs. Because of higher fitting precision and smaller error compared with the model I after training analysis and error analysis of verification set, model II can better predict soil moisture content in the Caragana brushland of loess hilly-gully region [15,16].

There were different change degrees of soil moisture in each soil layer. The changes of soil moisture content with soil depth gradually tend to be steady. The soil moisture in 100 cm soil layer was selected to forecast soil water content in other soil layers, and the soil moisture in 40 cm and 200 cm soil layer were choosing to generalize the model. All of obtained results were ideal.

If we obtain the maximum infiltration depth and the change of withering coefficient with soil depth and soil water resources use limit by plant, the amount of water stored within the maximum infiltration depth, in which the soil moisture content in each layer is equal to the withering coefficient before forecasting soil water content in the maximum infiltration depth in advance, we can estimate soil water resources within the maximum infiltration depth and then compare the soil water resources and soil water resources use limit by plant. If the soil water resources equal to soil water resources use limit by plant, soil drought is serious. At this stage of plant growth, the soil water seriously influences plant growth. The serious soil drought will cause soil degradation, plant death, crop failure, and waste land resource. In order to control the serious soil drought and obtain high production, we have to predict soil moisture content in the maximum infiltration depth and estimate soil water resources and soil water carrying capacity for vegetation, and then regulate the plant water relationship and improve the soil water condition by reducing plant density to increase the soil water supply from rainfall and reduce the soil water consumption if the soil water resources and soil water resources use limit by plant because soil water resources are renewable resources and only come from rainfall, there is not enough water resource to irrigation, and ground water is deep and cannot be used by plant. When regulate the relationship between soil water and plant growth, the amount of regulation equals the difference between present density minus soil water carrying capacity for vegetation to realize sustainable use of soil water resources [10].

## CONCLUSION

According to the wavelet analysis, NARX recursive neural network model established in this paper has higher prediction accuracy of soil water content, and can well predict soil moisture content at a given soil layers with various fluctuating frequency, and has better generalization performance. This is a good model to predict soil moisture in the brushland. The results provide powerful basis for soil drying control, regulation of the relationship between soil moisture and plant growth and sustainable use of soil water in the water-limited regions.

If we measured the maximum infiltration depth and the change of withering coefficient with soil depth, and estimated soil water resources, soil water resources use limit by plant in advance before predicting soil moisture content at a given soil layers, then we can take effective measure to control the soil degradation and vegetation decline by regulating the relationship between soil moisture and plant growth and realizing the sustainable use of soil water in the water-limited regions. This research needs to continue.

## ACKNOWLEDGEMENT

This study was supported by the National Science Fund of China (Project No. 41271539, 41071193) and National Key R and D plan (Project No. 2016YFC0501702).

## REFERENCES

1. Liu HB, Wu W, Wei CF. Study of soil water forecast with neural network. *J Soil Water Conserv.* 2003;17(5):59-62.
2. Lixi Z, Pengbo S, Fang J, et al. Using monitoring data of surface soil to predict whole crop-root zone soil water content with PSO-LSSVM, GRNN and WNN. *Earth Sci Inform.* 2014; 7:59-68.
3. Pisoni E, Farina M, Carnevale C, et al. Forecasting peak air pollution levels using NARX models. *Eng Appl Artif Intell.* 2009; 22(4-5):593-602.
4. Cai L, Ma S, Cai H, et al. Prediction of SYM-H index by NARX neural network from IMF and solar wind data. *Sci China Technol Sci.* 2009; 52:2877-2885.
5. Liu H, Xie D, Wu W. Soil water content forecasting by ANN and SVM hybrid architecture. *Environ Monit Assess.* 2008; 143:187-193.
6. Guo QC, He ZF. Forecast Model of Soil Water Content Based on Artificial Neural Network. *J Agric Sci.* 2012; 40:892-895.
7. Kseneman M, Gleich D, Potočnik B. Soil-moisture estimation from TerraSAR-X data using neural networks. *Mach Vis Appl.* 2012; 23:937-952.
8. Tingbing XU, Guangwen MA, Weibin HU, et al. BP network prediction model and its application in annual runoff forecasting based on wavelet analysis. *Water Resources and Power.* 2012; 30(2):17-19.
9. Guo Z. Soil Hydrology Process and Sustainable Use of Soil Water Resources in Desert Regions.
10. Lu ZJ, Zhu L, Pei HP, et al. The model of chlorophyll-a concentration forecast in the West Lake based on wavelet analysis and BP neural networks. *Acta Ecologica Sinica.* 2008; 10:4965-4973.
11. FAO/UNESCO. Soil map of the world, revised legend. 1988.
12. Yang WZ, Shao MA. Soil water research on the Loess Plateau., (Science Press: Beijing).
13. Zhou W, Gui L, Zhou L. High-level technology of MATLAB Wavelet Analysis. Xi'an: Xidian University. 2006;63.
14. Shi Y, Han LQ, Lian XQ. Neural Network Design and Instance Analysis. Beijing University of Posts and Telecommunications Press. 2009.
15. Jiang X, Liu C. Radial basis function networks based on wavelet analysis for the annual flow forecast. *J Appl Sci.* 2004; 22(3):411-414.
16. Zhang DF. MATLAB Wavelet Analysis (Second Edition). Mechanical Industry Press. Beijing. China. 2012.